



euroflood mini

IP65 asymmetric floodlight

Optics

- Lamp options:
 - 70W HQI-TS/CDM-TD
 - 150W HQI-TS/CDM-TD
 - 300W Tungsten Halogen
- Asymmetric light distribution for low light pollution
- Precise asymmetric optical control
- Hammered, high-grade aluminium reflector, brightened and anodised
- Toughened glass

Body

- IP65
- Precision diecast aluminium low profile design
- Polyester powder coat finished in black or white
- Mounting by cradle supplied
- Attachments:
 - Uplighter bracket (interior applications)
 - Wire guard
- Takes supply cable of 5-10mm diameter
- Timed ignitor
- Can be used in uplight or downlight orientation



euroflood mini

> weblink > **MINI**

ORDER CODES

Euroflood Mini (Black)

HQI-TS/CDM-TD 70W	SC70/B
HQI-TS/CDM-TD 150W	SC150/B
TUNGSTEN HALOGEN 300W	SC300/B


Options

WHITE	Replace B with W in order code	i.e. SC70/ W
WIRE GUARD		SCWCMN
UPLIGHTER BRACKET BLACK		SCUBMN
UPLIGHTER BRACKET WHITE		SCUBMN/W

LAMP PERFORMANCE

Wattage	IL@25°C	Lamp Life
70W CDM-TD	6600	12,000hrs
70W HQI-TS	5500	10,000hrs
150W CDM-TD	14000	12,000hrs
150W HQI-TS	12900	12,000hrs
300W TH	5000	2,000hrs

DIMENSIONS




Version	L	W	H	KG
SC70	235	88	350	6.0
SC150	235	88	350	6.5

WINDAGE

VERSION	WATTAGE	WINDAGE*
SC70	70W	0.03m²
SC150	150W	0.03m²

*Figures are given for the typical mounting position i.e. side windage

PHOTOMETRIC PERFORMANCE



1 x 70W
CDM-TD/HQI-TS
• LOR = 68%




White



Wire guard



Uplighter bracket



Uplighter bracket

TO SPECIFY

Die cast aluminium precision floodlight with asymmetric beam. Body <89mm deep 70/150W HQI-TS/CDM-TD lamp. IP65 – as Whitecroft Lighting EUROFLOOD MINI