

euroflood zx

> weblink > EUZX

Optics

- Lamp options:
 - 1 x 150/250/400W HQI-T
- Anodised aluminium reflector with asymmetric distribution to minimise light pollution
- Tempered glass cover sealed to the body

Body

- Die cast aluminium body, finished grey. Heat dissipating wall separates the gear from lamp
- Extruded aluminium mounting bracket finished grey
- IP66
- Optional protective wire guard for glass, barn door visor and anti-glare grid




ORDER CODES

Euroflood ZX	HF Gear
HQI-T 150W	EZX150H
HQI-T 250W	EZX250H
HQI-T 400W	EZX400H
Options	
Wire guard	EZXWG
Anti-glare grid	EZXAGG
Barn-door visor	EZXBDV

LAMP PERFORMANCE

Wattage	IL@25°C	Lamp Life
1 x 150W HQI-T	13000	9,000hrs
1 x 250W HQI-T	20000	9,000hrs
1 x 400W HQI-T	36000	9,000hrs

PHOTOMETRIC PERFORMANCE



Anti-glare grid




Wire guard



Barn-door visor

DIMENSIONS



Version	L	W	H	KG	WINDAGE
150/250W	435	175	600	13.0	0.23m ²
400W	435	175	600	14.5	0.23m ²

TO SPECIFY

IP66 asymmetric floodlight for HQI-T lamps. Cast aluminium body with heat dissipating wall to separate gear from the lamps, anodised aluminium asymmetric reflector and tempered glass cover – as Whitecroft Lighting EUROFLOOD ZX

