

exit

Emergency: Indoor exit sign



APPLICATION

- Exit doors – interior
- Offices
- Hotels
- Wherever traditional exit signs are used

SPECIFICATION

- Supplied with 8W T5 lamp
- Rigid white powder coated steel housing and gear and lamp tray. Substantial downlight panels in body designed to give illumination at floor level
- Screen printed legend panels retained by screw fixed front frame – please see page 190 to order
- Viewing distances up to 30m when using legend panel
- IP20
- 3 hour self contained maintained or non-maintained versions
- High temperature Ni-Cd battery with constant current charger and LED charge indicator
- Cable entry via knockouts sides and rear
- Ambient 0° to 25°C
- Designed and manufactured to meet the requirements of BS EN60598.2.22

FEATURES

	SEN/EX/NM/F8	SEN/EX/M/F8
MODE	Non-maintained	Maintained
DURATION	3 hours	
INPUT VOLTAGE	230/240V – 50Hz	
CIRCUIT WATTS	8W	20W
BATTERY TYPE	High temperature Ni-Cd battery	
RECHARGE TIME	24 hours	

DIMENSIONS



ORDER CODES – EXIT

EMERGENCY INDOOR EXIT SIGN

LAMP SUPPLIED	EMERGENCY LIGHTING	EMERGENCY UNIT
1 x 8W T5	3 hour non maintained	SEN/EX/NM/F8
1 x 8W T5	3 hour maintained	SEN/EX/M/F8

LEGEND PANELS Order separately

See page 190 to specify

EASYTEST OPTION Add suffix to order code above

/ET Integral self autotest, i.e. **SEN/EX/NM/F8/ET**

To specify state:

8W T5 IP20, 3 hour self contained maintained or non-maintained emergency exit sign with rigid White powder coated steel body and gear and lamp tray. Screen printed legend panels retained by screw fixed front frame. High temperature Ni-Cd battery with constant current charger and LED charge indicator – as Whitecroft Lighting EXIT

Options

- Easytest – integral self test version available see page 181

QuickLink

EXIT

Go