

## Optics

- Max 30m viewing distance
- Lamp options:
  - 1 x 8W T5
- Screen printed legend panel retained by screw fixed front frame to be ordered separately
- Legends supplied in accordance with BS 5266-1 2011 (ISO7010)

## Body

- Rigid white powder coated steel housing and gear and lamp tray. Substantial downlight panels in body designed to give illumination at floor level
- 3 hour maintained or non-maintained versions
- High temperature Ni-Cd battery with constant current charger and LED charge indicator
- Cable entry via knockouts in sides and rear
- Ambient 0° – 25°C
- Circuit Watts 8W (20W maintained version)



## Order Codes

| Exit      |                       | 3 hr Emergency |
|-----------|-----------------------|----------------|
| T5 1 x 8W | 3 hour non-maintained | SENEXNMF8      |
| T5 1 x 8W | 3 hour maintained     | SENEXMF8       |


## Options

|              |                |                   |
|--------------|----------------|-------------------|
| EASYTEST     | Add suffix /ET | i.e. SENEXNMF8/ET |
| COMEPS       | Add suffix /EP | i.e. SENEXNMF8/EP |
| LEFT LEGEND  |                | SENLP/7010        |
| RIGHT LEGEND |                | SENLP/7010        |
| DOWN LEGEND  |                | SENLPD/7010       |
| UP LEGEND    |                | SENLP/7010        |

Note: Legends to be ordered separately

Available with COMET. Please refer to our sales office for details

## Dimensions



## Legends



Up

Down



Left

Right

## To Specify

8W T5 IP20, 3 hour self contained maintained or non-maintained emergency exit sign with rigid white powder coated steel body and gear and lamp tray. Screen printed legend panels retained by screw fixed front frame. High temperature Ni-Cd battery with constant current charger and LED charge indicator – as Whitecroft Lighting EXIT