

Optics

- Power consumption:
 - 3W maintained
 - 1.5W non maintained
- 16 x low energy LEDs
- 34m viewing distance
- Product is supplied as a complete unit with opal polycarbonate legend panel already fitted
- Up, down, left and right legend panels are available
- Legends supplied in accordance with BS 5266-1 2011 (ISO7010)

Body

- Wall mounted via key hole slot fixings
- Steel body finished white
- Two part body for ease of installation, cover hooks over the back plate and is simply retained below
- High temperature Ni-Cd battery with constant current charger and LED charge indicator
- 3 hour maintained (may be wired as non-maintained)
- BESA cable entry



Order Codes

Exit LED

3W, with UP legend supplied
 3W, with LEFT legend supplied
 3W, with RIGHT legend supplied
 3W, with DOWN legend supplied

Product Code

EXM7010U
 EXM7010L
 EXM7010R
 EXM7010D


Options

COMEPS* Add suffix /EP

i.e. EXM7010U/EP

*Can be wired as Easytest if required

Dimensions



L	W	H	KG
385	71	185	2.4

Legends



Up



Down



Left



Right

To Specify

3W LED IP20, 3 hour self-contained maintained emergency exit sign with rigid white powder coated steel body and opal polycarbonate legend. High temperature Ni-Cd battery with constant current charger and LED charge indicator - as Whitecroft Lighting EXIT LED