



### Optics

- Lamp options:
  - 2 x 36W TC-L
  - 2 x 40W TC-L
  - 2 x 55W TC-L
  - 3 x 55W TC-L
  - 4 x 55W TC-L
- Light distribution: 80% up and 20% down
- Downlight controller white perforated steel

### Body

- Extruded aluminium and fabricated steel construction finished matt metallic grey




### Order Codes

| Flight       | HF Gear   |
|--------------|-----------|
| TC-L 2 x 36W | FLTW2369H |
| TC-L 2 x 40W | FLTW2409H |
| TC-L 2 x 55W | FLTW2559H |
| TC-L 3 x 55W | FLTW3559H |
| TC-L 4 x 55W | FLTW4559H |

### Options

|                |                  |                |
|----------------|------------------|----------------|
| DALI DIMMING   | Replace H with Y | i.e. FLTW2369Y |
| SWITCH DIMMING | Replace H with X | i.e. FLTW2369X |

### Photometric Performance



- 2 x 55W TC-L
- LOR = 62.8%
- SHR MAX = 1.26


### Lamp Performance

| Wattage      | IL@25°C | Lamp Life |
|--------------|---------|-----------|
| 1 x 36W TC-L | 2900    | 20,000hrs |
| 1 x 40W TC-L | 3500    | 20,000hrs |
| 1 x 55W TC-L | 4800    | 20,000hrs |

### Utilisation Factors UF(F)

| Room Reflectance | Room Index     |
|------------------|----------------|
| C W F            | 1.00 3.00 5.00 |
| 0.70 0.50 0.20   | 0.31 0.47 0.51 |

### Dimensions



| Version    | L   | W   | H  | KG  |
|------------|-----|-----|----|-----|
| 2 x 36W    | 495 | 274 | 72 | 5.0 |
| 2 x 40/55W | 615 | 274 | 72 | 5.4 |
| 3 x 55W    | 615 | 274 | 72 | 5.5 |
| 4 x 55W    | 615 | 395 | 72 | 6.5 |

### To Specify

Wall mounted uplighter extruded aluminium and fabricated steel. 72mm in depth. 80% uplight, 20% downlight – as Whitecroft Lighting FLIGHT