





Optics

- Lamp options (1200mm body):
 - 1 x 54W T5 uplighter (ward lighting)
 - 1 x 54W T5 downlighter (reading/nursing care)
- Lamp options (600mm body):
 - 1 x 55W TC-L uplighter (ward lighting)
 - 1 x 55W TC-L downlighter (reading/nursing care light)
- Removable diffusers for both ward and reading/nursing care lights run the full length of the body to optimise light distribution
- Both the ward and reading lamps are independently dimmable by “push control” and function so the following lighting levels can be selected to meet LG2 requirements:
 - Patient rest 30-50 Lux
 - Watch light 15-20 Lux
 - Reading 300 Lux
 - General nursing care 300 Lux

Body

- Extruded aluminium body and full length wall bracket with closed ends finished white
- Wall mounted, recommended mounting height 2m for typical 2.6m-3m ceiling heights
- 1st fix wall bracket, pre-wired to GST 18/4 flying leads



Mounting Bracket



End Section


Order Codes

Florence	Standard
T5 2 x 54W (one for the ward and one for the reading light)	FLRX5454
TC-L 2 x 55W (one for the ward and one for the reading light)	FLRX5555

Lamp Performance


Wattage	IL@25°C	Lamp Life
1 x 54W T5	4450	24,000hrs
1 x 55W TC-L	4800	20,000hrs

Dimensions




Version	L	W	H	KG
2 x 55W TC-L	580	322	100	7.0
2 x 54W T5	1188	322	100	10.0

Typical 4 Bed Ward



Typical 1 Bed Ward



Ⓜ Nightingale recommended for circulation area lighting

To Specify

Direct/Indirect wall mounted hospital bed-head luminaire with 2 x 54W T5 or 2 x 55W TC-L separately switched lamps one lamp providing ward lighting the other reading/nursing care light. Extruded aluminium body and wall bracket with profiled end caps and full length polycarbonate diffusers. Lamps to be independently dimmed by ‘push control’ – as Whitecroft Lighting FLORENCE