

glide

architectural suspended luminaire

> weblink > **GLIW**

Optics

- Lamp options:
 - 1 or 2 x 28/35/49/54W T5
- MIRO 6 semi-specular louvre
- Light distribution, 80% down and 20% up

Body

- Steel body finished white or silver
- Low profile body designed for individual mounting
- Includes a 2 wire adjustable (max 1.5m) suspension kit with polycarbonate colour coded ceiling cover



ORDER CODES

Glide	HF Gear	3 hr Emergency
T5 1 x 28W	GLIW5H128S	GLIW5H128SEMIN
T5 2 x 28W	GLIW5H228S	GLIW5H228SEMIN
T5 1 x 35W	GLIW5H135S	GLIW5H135SEMIN
T5 2 x 35W	GLIW5H235S	GLIW5H235SEMIN
T5 1 x 49W	GLIW5H149S	GLIW5H149SEMIN
T5 2 x 49W	GLIW5H249S	GLIW5H249SEMIN
T5 1 x 54W	GLIW5H154S	GLIW5H154SEMIN
T5 2 x 54W	GLIW5H254S	GLIW5H254SEMIN

Options


DALI DIMMING	Replace H with Y in order code	i.e. GLIW5 Y 128S
DSI DIMMING	Replace H with D in order code	i.e. GLIW5 D 128S
SWITCH DIMMING	Replace H with X in order code	i.e. GLIW5 X 128S
COMMAND 4	Replace H with Q4Y in order code	i.e. GLIW5 Q4Y 128S
EASYTEST	Add suffix /ET to order code	i.e. GLIW5H128S/ ET
COMET	Add suffix /CT to order code	i.e. GLIW5H128S/ CT
WHITE FINISH	Replace S with W in order code	i.e. GLIW5H128 W



LAMP PERFORMANCE


Wattage	IL@25°C	Lamp Life
1 x 28W T5	2600	24,000hrs
1 x 35W T5	3300	24,000hrs
1 x 49W T5	4300	24,000hrs
1 x 54W T5	4450	24,000hrs

DIMENSIONS




Version	L	W	H	KG	KG/m²
28/54W	1330	250	58	7.0	8.0
35/49W	1630	250	58	7.0	8.0

PHOTOMETRIC PERFORMANCE



- 1 x 54W T5
- LOR = 81%
- SHR MAX = 1.54



- 2 x 54W T5
- LOR = 60%
- SHR MAX = 1.31

Utilisation Factors UF(F)

Room Reflectance			Room Index		
C	W	F	1.00	3.00	5.00
0.70	0.50	0.20	0.61	0.77	0.81

Utilisation Factors UF(F)

Room Reflectance			Room Index		
C	W	F	1.00	3.00	5.00
0.70	0.50	0.20	0.40	0.54	0.58

PERFORMANCE GUIDE

Lamps	Illuminance	Spacing
2 x 54W T5	500 lux	3.0m x 3.0m

Maintenance: 0.8
Reflectance: 70/50/20
Ceiling Height: 2.7m
Working Plane: 0.8m

TO SPECIFY

Suspended T5 fluorescent luminaire with direct/indirect lighting ratio 80% down and 20% up. Positively retained MIRO 6 zero iridescence louvre and integral gear on a detachable tray. 58mm deep. Adjustable twin wire suspension with injection moulded polycarbonate ceiling rose cover – as Whitecroft Lighting GLIDE

