

iceberg LED

cubic decorative LED luminaire



Optics

- Output:
– 3900 lumens, 33W
- Opal white polypropylene shade masking the lamp image

Body

- Available as suspended or surface mounted
- Suspended product comes supplied with 4-point wire suspension kit and mains feed cable with ceiling rose
- IP20
- Suspended product has max. drop of 2m



Order Codes

Iceberg LED

Suspended, 3900lm (33W)

Surface, 3900lm (33W)

Fixed Output

903.53.2.09.1

903.53.2.09.0


Options

DALI

Add suffix .DALI


i.e. 903.53.2.09.1.DALI

Dimensions



L	W	W ₁	H	KG
435	435	365	190	3.6

Photometric Performance



33W LED (4K)
3900 lumens
• LOR = 100%
• SHR MAX = 1.66

Utilisation Factors UF(F)

Room Reflectance			Room Index		
C	W	F	1.00	3.00	5.00
0.70	0.50	0.20	0.56	0.83	0.91

LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000K	Ra>80	L ₇₀ (50,000hrs)	MacAdam 3 SDCM

To Specify

Cubic decorative LED luminaire with opal polypropylene shade
– as Whitecroft Lighting ICEBERG LED