



Optics

- Lamp options:
 - 1 or 2 x 28/35/49/54/80W T5

Body

- Steel batten finished white
- Polycarbonate injection moulded end caps
- Supplied with iTrack 7 pole adapter which enables:
 - Rapid installation
 - Easy access for maintenance
- Compatible with iTrack Line reflectors and attachments, please order separately
- See iTrack emLED for emergency requirements



Line Twin

Order Codes

iTrack Line Single

T5 1 x 28W
T5 1 x 35W
T5 1 x 49W
T5 1 x 54W
T5 1 x 80W

HF Gear
ITRLH128
ITRLH135
ITRLH149
ITRLH154
ITRLH180

iTrack Line Twin

T5 2 x 28W
T5 2 x 35W
T5 2 x 49W
T5 2 x 54W
T5 2 x 80W

HF Gear
ITRLH228
ITRLH235
ITRLH249
ITRLH254
ITRLH280


Options

DALI DIMMING

Replace H with Y

i.e. ITRLY128

Dimensions




Version	L	W	H	KG
28/54W	1183	51.5	74	1.4
35/49/80W	1483	51.5	74	1.8

Performance Guide

Luminaire with medium reflector

Lamps Illuminance Spacing
1 x 54W T5 450 lux 3.0m x 3.0m



Maintenance:
0.8
Reflectance:
70/50/20
Ceiling Height:
3m
Suspension:
0.5m
Working Plane:
0.8m

Lamp Performance

Wattage	IL@25°C	Lamp Life
1 x 28W T5	2625	24,000hrs
1 x 35W T5	3325	24,000hrs
1 x 49W T5	4375	24,000hrs
1 x 54W T5	4450	24,000hrs
1 x 80W T5	6550	24,000hrs

To Specify

T5 fluorescent steel batten with polycarbonate end caps. Track phase selection to be located on the luminaire with twist locking rotary toggle for efficient installation and maintenance – as Whitecroft Lighting iTRACK LINE