



### Optics

- Lamp options:
  - 1 or 2 x 28/35/49/54/80W T5

### Body

- Steel batten finished white
- Polycarbonate injection moulded end caps
- Supplied with iTrack 7 pole adapter which enables:
  - Rapid installation
  - Easy access for maintenance
 (Emergency luminaire supplied with 8 pole adapter)
- Compatible with iTrack Line reflectors and attachments, please order separately



Line Twin

### Order Codes


| iTrack Line Single | HF Gear  | 3 hr Emergency |
|--------------------|----------|----------------|
| T5 1 x 28W         | ITRLH128 | ITRLH128EM     |
| T5 1 x 35W         | ITRLH135 | ITRLH135EM     |
| T5 1 x 49W         | ITRLH149 | ITRLH149EM     |
| T5 1 x 54W         | ITRLH154 | ITRLH154EM     |
| T5 1 x 80W         | ITRLH180 | -              |

| iTrack Line Twin | HF Gear  | 3 hr Emergency |
|------------------|----------|----------------|
| T5 2 x 28W       | ITRLH228 | ITRLH228EM     |
| T5 2 x 35W       | ITRLH235 | ITRLH235EM     |
| T5 2 x 49W       | ITRLH249 | ITRLH249EM     |
| T5 2 x 54W       | ITRLH254 | ITRLH254EM     |
| T5 2 x 80W       | ITRLH280 | -              |

### Options

|              |                  |                  |
|--------------|------------------|------------------|
| DALI DIMMING | Replace H with Y | i.e. ITRLY128    |
| EASYTEST     | Add suffix /ET   | i.e. ITRLH128/ET |
| COMEPS       | Add suffix /EP   | i.e. ITRLH128/EP |


### Dimensions



| Version   | L    | W    | H  | KG  | KG  |
|-----------|------|------|----|-----|-----|
| 28/54W    | 1183 | 51.5 | 74 | 1.4 | 2.2 |
| 35/49/80W | 1483 | 51.5 | 74 | 1.8 | 2.6 |

### Performance Guide

| Luminaire with medium reflector |             |             |
|---------------------------------|-------------|-------------|
| Lamps                           | Illuminance | Spacing     |
| 1 x 54W T5                      | 450 lux     | 3.0m x 3.0m |



Maintenance:  
0.8  
Reflectance:  
70/50/20  
Ceiling Height:  
3m  
Suspension:  
0.5m  
Working Plane:  
0.8m

### Lamp Performance

| Wattage    | IL@25°C | Lamp Life |
|------------|---------|-----------|
| 1 x 28W T5 | 2625    | 24,000hrs |
| 1 x 35W T5 | 3325    | 24,000hrs |
| 1 x 49W T5 | 4375    | 24,000hrs |
| 1 x 54W T5 | 4450    | 24,000hrs |
| 1 x 80W T5 | 6550    | 24,000hrs |

### To Specify

T5 fluorescent steel batten with polycarbonate end caps. Track phase selection to be located on the luminaire with twist locking rotary toggle for efficient installation and maintenance – as Whitecroft Lighting iTRACK LINE