

# JLE escalator


**Industrial:** Escalator balustrade lighting

## APPLICATION

- Escalators
- Moving walkways


## SPECIFICATION

- London Underground Ltd. (LUL) approved
- Designed for 40 year life span
- Lamp option:
  - 1 x 26W TC-T
- IP65 construction
- Highly vandal resistant
- Body: Cast aluminium
- Door: Hinged stainless steel bezel glazed with toughened safety glass
- Lens: Faceted toughened glass
- Access via 3, stainless steel, allen key screws
- High frequency control gear
- Specify cable entry requirements
- Weight 3.5kg
- Supplied with lamp



Access via hinged door

## DIMENSIONS




## PHOTOMETRY

**JLE Escalator**  
TYPE 30  
1 x 26W TC-T



- SHR MAX= 1.28
- LOR = 22.2%



| UTILISATION FACTORS UF(F) |            |      |      |      |      |      |      |      |      |      |      |  | SHR NOM=N/A |
|---------------------------|------------|------|------|------|------|------|------|------|------|------|------|--|-------------|
| Room Reflectance          | Room Index |      |      |      |      |      |      |      |      |      |      |  |             |
| C                         | W          | F    | 0.75 | 1.00 | 1.25 | 1.50 | 2.00 | 2.50 | 3.00 | 4.00 | 5.00 |  |             |
| 0.70                      | 0.50       | 0.20 | N/A  | N/A  | 0.12 | 0.13 | 0.15 | 0.16 | 0.17 | 0.18 | 0.19 |  |             |
| 0.50                      | 0.30       | 0.20 | N/A  | N/A  | 0.09 | 0.10 | 0.11 | 0.12 | 0.13 | 0.14 | 0.15 |  |             |
| 0.00                      | 0.00       | 0.00 | N/A  | N/A  | 0.05 | 0.05 | 0.06 | 0.07 | 0.08 | 0.09 | 0.09 |  |             |

## ORDER CODES - JLE ESCALATOR

ESCALATOR BALUSTRADE LIGHTING

### LAMP SUPPLIED

1 x 26W TC-T

### LUMINAIRE

**TUEX126TH**

## LAMP PERFORMANCE MATRIX

| WATTAGE      | IL@25°C | LAMP LIFE |
|--------------|---------|-----------|
| 1 x 26W TC-T | 1800    | 10,000    |

*To specify state:*

LUL approved, cast aluminium compact fluorescent luminaire with hinged stainless steel bezel and glazed with toughened safety glass, 40 years design life and rated IP65 – as Whitecroft Lighting JLE ESCALATOR

QuickLink

JLEE

Go