

Kolo IP65 hood

IP65 LED surface mounted
amenity luminaire with hood



Optics

- Light output options:
 - 1008 lumen, 14W
- Polycarbonate opal diffuser
- 'Cool' white 4000K colour temperature

Body

- Surface mounted
- 400mm diameter in cast aluminium with injection moulded base
- IP65
- Finished in silver or black
- Choice of integrated emergency options:
 - 3 hour emergency
 - COMEPS
- Trim ring supplied as standard



Order Codes

Kolo IP65 Hood
1008 lumens (14W)

Fixed Output
K6H44KHB

3 hr Emergency
K6H44KHBEM


Options

Silver
DALI
COMEPS

Replace B with **S**
Replace H with **Y**
Add suffix **EP**


i.e K6H44KHS
i.e K6Y44KHB
i.e K6H44KHBEP

Dimensions



Version	Ø	W	KG	KG
400mm Ø	400	95	4.0	4.5

Photometric Performance



14W LED
1008 lumens
• LOR = 100%

LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000K	Ra>80	L ₈₀ (50,000hrs)	MacAdam 3 SDCM

Equivalent Lamp Types

1008 Lumen Output
2D lamp

1 x 28W

To Specify

Surface mounted circular IP65 LED bulkhead luminaire in 400mm diameter. Polycarbonate opal diffuser. Supplied with trim ring – as Whitecroft Lighting KOLO IP65 HOOD