



Optics

- Lamp options:
 - 1 x 28W 2D
 - 1 x 38W 2D
- Etched glass outer ring supported by 3 chrome pillars
- White opal glass diffuser giving halo effect

Body

- Spun steel body, finished in white
- Wall or ceiling mounting



Order Codes


Laguna	HF Gear	3 hr Emergency
2D 1 x 28W	LNH128	LNH128EM
2D 1 x 38W	LNH138	LNH138EM

Options

EASYTEST	Add suffix /ET	i.e. LNH128/ET
COMEPS	Add suffix /EP	i.e. LNH128/EP
COMET	Add suffix /CT	i.e. LNH128/CT

Performance Guide

Lamps	Illuminance	Spacing
1 x 38W	230 lux	2.4m x 2.4m




Maintenance:
0.8
Reflectance:
70/50/20
Ceiling Height:
2.7m
Working Plane:
0.8m


Lamp Performance

Wattage	IL@25°C	Lamp Life
1 x 28W 2D	2150	21,000hrs
1 x 38W 2D	3020	21,000hrs

Dimensions



Photometric Performance



1 x 28W 2D
• LOR = 56.9%
• SHR MAX = 1.67

Utilisation Factors UF(F)

Room Reflectance	Room Index
C W F	1.00 3.00 5.00
0.70 0.50 0.20	0.34 0.50 0.54

To Specify

Surface mounted circular 2D luminaire 420mm Ø and 100mm protrusion from surface. White opal glass diffuser with etched outer glass ring. Spun steel body – as Whitecroft Lighting LAGUNA