

LDR IP65

Downlighters: Low voltage downlighters

APPLICATION

- Wash rooms and shower rooms
- Retail applications
- Food display areas
- High humidity areas
- Under canopy applications
- Hotels
- Exhibition stands

SPECIFICATION

- Lamp options:
 - 20W, 35W or 50W dichroic low voltage GU5.3 lamp base
- Die-cast aluminium housing
- Opaque safety glass front
- Wing fixing
- Lamp replacement from outside the ceiling void
- Supplied complete with dimmable IP20 electronic transformer
- Recess depth only 100mm
- Supplied without lamp
- For ceiling thickness
 - 3.0mm - 20mm




LDR9105-IP65



LDR9102-IP65

DIMENSIONS





ORDER CODES – LDR IP65

RECESSED IP65 LOW VOLTAGE DOWNLIGHTER

SUPPLIED WITH TRANSFORMER LESS LAMP	TRIM	LDR IP65
IP65	White	LDR9102-IP65
	Chrome	LDR9105-IP65

To specify state:

Recessed low voltage 50W downlight with bezel Ø <85mm recess and depth <100mm. Die cast aluminium body complete with dimmable electronic transformer. IP65 from below ceiling – as Whitecroft Lighting LDR IP65

QuickLink

LDRI

Go