

LDR micro

Downlighters: Low voltage downlighters

APPLICATION

- Retail
- Reception areas
- Domestic applications
- Conference rooms
- Art galleries


SPECIFICATION

- Lamp options:
 - 20W, 35W or 50W dichroic low voltage GU5.3 lamp base
- Body – die cast aluminium
- Bezel – white or chrome
- Supplied complete with dimmable electronic transformer
- Ceiling retention by wing mechanism
- For ceiling thickness – 3.0mm to 17mm
- Quick release lamp change
- Supplied without lamp
- Available in fixed and tilt version




DIMENSIONS

LDR Micro



LDR Micro Tilt



PHOTOMETRY

50W DICHROIC

Angle 36°

12V 50MM Ø

HGT	LUX	Ø
1.0m	1800	0.9m
2.0m	450	1.3m
3.0m	200	2.0m
4.0m	110	2.6m



LDR9172



LDR9102



LDR9105



LDR9175

ORDER CODES – LDR MICRO

LOW VOLTAGE DOWNLIGHTERS

LDR MICRO	SUPPLIED WITH TRANSFORMER LESS LAMP	TRIM
LDR9102	Micro	White
LDR9105		Chrome
LDR9172	Micro Tilt	White
LDR9175		Chrome

To specify state:

Recessed directional low voltage downlight with die cast aluminium ceiling bezel
supplied complete with dimmable electronic transformer – as Whitecroft Lighting
LDR MICRO

QuickLink

LDRC

Go