

LDR mini

Downlighters: Low voltage downlighters



LDR9202 – Mini



LDR9252 – Mini Decor



LDR9275 – Mini Wall



LDR92E2 – Mini Emergency

APPLICATION


- Retail
- Wallwashing
- Signage
- Museums
- Art galleries
- Reception areas
- Conference rooms
- Pictures
- Wall hangings
- Signage
- Details and features
- Wall texture
- Domestic application

SPECIFICATION

- Lamp options:
 - 20W, 35W or 50W dichroic
 - low voltage GU5.3 lamp base
- Body – die cast aluminium
- Bezel – White or chrome
- LDR Mini Decor: Floating glass trim with central hole
- LDR Mini Wall: Rotates through 355°, 60° vertical adjustment
- The LDR92E2 is supplied complete with emergency kit comprising of a charger unit and a series of maintenance free sealed lead acid batteries in a flame retardant sleeve. The kit will pass through an 80mm Ø cut-out. Maintains a 50W lamp for 3 hours at reduced output
- Supplied complete with dimmable electronic transformer
- Ceiling retention by wing mechanism
- For ceiling thickness – 3.0mm to 22mm
- Quick release lamp change
- Supplied without lamp

DIMENSIONS

LDR Mini



PHOTOMETRY

50W DICHROIC
12V 50MM Ø

Angle 36°

HGT	LUX	Ø
1.0m	1800	0.9m
2.0m	450	1.3m
3.0m	200	2.0m
4.0m	110	2.6m



ORDER CODES – LDR MINI

LOW VOLTAGE DOWNLIGHTERS

LDR MINI	SUPPLIED WITH TRANSFORMER LESS LAMP	TRIM
LDR9202	LDR Mini	White
LDR9205		Chrome
LDR9252	LDR Mini Decor	White
LDR9255		Chrome
LDR9272	LDR Mini Wall	White
LDR9275		Chrome
LDR92E2*	LDR Mini Emergency	White

* Note: Emergency versions run at reduced output in emergency mode

QuickLink

LDRM

Go

To specify state:

Recessed directional low voltage downlight with die cast aluminium ceiling bezel supplied complete with dimmable electronic transformer. Optional emergency, decor and wall wash versions – as Whitecroft Lighting LDR MINI