

Marine LF

In Ground recessed fixed uplighter for outdoor applications



IK08

IP67



Optics

- Light output options:
 - 464 lumens (4000K – 4.0W)
- Symmetrical distribution with 25 degree beam
- Thermal shock and impact resistant, tempered glass

Body

- Fibreglass & nylon housing
- Stainless steel frame (316 grade)
- IP67 IK08 rated protection
- Suitable for setting into concrete as standard
- Optional mounting ring for wall or wooden floors (order separately)
- Remote driver in IP67 rated enclosure required (order separately) - maximum 4 luminaires per driver

Order codes

Marine LF

		LL/CW	L70
LED 464 lumens (4.0W)	MRLF33M	116	60k


Accessories

Driver in watertight enclosure (max 4 luminaires)	MRPS
Optional mounting ring	DS/99392600

LED Performance


Colour Temp	RA (CRI)	Colour consistency
4000K	>80	MacAdam 3 SDCM

Dimensions



	L	W	H	KG	Ø
Body	n/a	n/a	86	0.4	120
Gear box	240	160	115	1.5	n/a

Photometric Performance



3.8W 300 Lumen
LOR = 100.0%

To Specify

IP67 In Ground recessed LED uplighter with stainless steel frame. With medium beam symmetrical distribution – as Whitecroft Lighting MARINE LF
