

micro spot 65

IP65 surface mounted LED spotlight for feature lighting



Optics

- 1250 lumens, 14W
- 3000K LED
- Ra90 colour rendition
- Medium beam distribution
- LED life 50,000 hours to 70% L70B50

Body

- IP65, IK08 protection rated
- Die cast aluminium body
- Polyester powder coated
- Graphite grey or silver finish
- Tempered glass diffuser
- Adjustable aiming direction
- Surface mounting
- Optional mounting 'spike' for installation into soft ground
- Fitted cable gland
- Fixed output LED driver

Order Codes

Graphite Grey
1250 lumen, 14W

Fixed Output
MCLH13KG

Options

SILVER FINISH
4000K LED ON REQUEST

Replace G with S

i.e. MCLH13KS

Accessories

GROUND MOUNTING SPIKE

MCLSPIKE




Silver finish




Ground mounting spike

Photometric Performance



14W, 1250 lumen
3000K
• LOR = 100%

Dimensions



H	Ø	Ø ₁	KG
194	127	114	0.77

LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
3000K	90	L ₇₀ (50,000hrs)	MacAdam 3 SDCM

To Specify

Surface mounted IP65 die cast aluminium LED spotlight with medium beam distribution. Finished in polyester powder coated graphite grey or silver – as Whitecroft MICRO SPOT 65

Outdoor