

mini spot 65

IP65 surface mounted LED spotlight for feature lighting



Optics

- 4000K LED
- Light output options:
 - Nominal 2100 lumens, 30W
 - Nominal 3200 lumens, 42W
- Ra90 colour rendition
- Wide and narrow beam distribution options
- LED life 50,000 hours to 70% L70B50

Body

- IP65, IK08 protection rated
- Die cast aluminium body
- Polyester powder coated
- Graphite grey or silver finish
- Tempered glass diffuser
- Adjustable aiming direction with protractor scale
- Surface mounting
- Optional mounting 'spike' for installation into soft ground
- Optional coloured filters (recommended for use with narrow beam version)
- Optional cowl or shutter for light control
- Supplied with IP rated cable gland
- Fixed output LED driver



Silver finish



Ground mounting spike



Shutter and cowl accessories



Coloured filters

Order Codes

Graphite Grey	Beam	Fixed Output
2119 lumen, 30W	Narrow beam	MNLH14KNG
3531 lumen, 42W	Narrow beam	MNLH24KNG
2140 lumen, 30W	Wide beam	MNLH14KWG
3198 lumen, 42W	Wide beam	MNLH24KWG


Options

SILVER FINISH	Replace G with S	i.e. MNLH14KNS
RGB COLOUR CHANGE	Available on request	

Accessories

GROUND MOUNTING SPIKE (2 PER LUMINAIRE WHERE REQUIRED)	MCLSPIKE
COWL ACCESSORY	MNLCOWL
SHUTTER ACCESSORY	MNLSHUTTER
FILTER ATTACHMENT – BLUE	MNLFBUE
FILTER ATTACHMENT – RED	MNLFRED
FILTER ATTACHMENT – GREEN	MNLFGREEN
FILTER ATTACHMENT - YELLOW	MNLFYELLOW

Dimensions




H	L	Ø	KG
260	220	150	2.7


LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000K	90	L ₇₀ (50,000hrs)	MacAdam 3 SDCM

Photometric Performance



Narrow beam
42W, 3531 lumen
4000K
• LOR = 100%



Wide beam
42W, 3198 lumen
4000K
• LOR = 100%

Outdoor

To Specify

Surface mounted IP65 die cast aluminium LED spotlight with narrow or wide beam distribution. Finished in polyester powder coated graphite grey or silver – as Whitecroft MINI SPOT 65