

mistral Q

IP54 amenity lighting for open spaces

> weblink > MISQ

Optics

- Lamp options:
 - 150/250/400W SON-T
 - 250/400W HQL-T

Body

- Aluminium housing and diffuser frame and die cast aluminium mounting bracket
- High purity anodised aluminium reflector
- Diffuser in 5mm thick thermal – shock resistant tempered glass
- IP54
- Polyester powder coat, finished in black
- Suitable for an ambient temperature between -25°C to +35°C
- Fits 60mm diameter column spigot



ORDER CODES


Mistral Q

SON-T 150W	MIQ150S
SON-T 250W	MIQ250S
SON-T 400W	MIQ400S
HQL-T 250W	MIQ250H
HQL-T 400W	MIQ400H

LAMP PERFORMANCE


Wattage	IL@25°C	Lamp Life
150W SON-T	15000	24,000hrs
250W SON-T	28000	18,000hrs
250W HQL-T	20000	9,000hrs
400W SON-T	48000	24,000hrs
400W HQL-T	32000	9,000hrs

DIMENSIONS



Version	L	W	H	KG	WINDAGE
MIQ150	560	390	190	13.0	0.22m ²
MIQ250	560	390	190	14.0	0.22m ²
MIQ400	560	390	190	15.0	0.22m ²

PHOTOMETRIC PERFORMANCE



1 x 250W SON-T
• LOR = 38.8%

TO SPECIFY

IP54 post top luminaire delivering a wide bi-symmetrical forward throw and supplied with 150, 250 or 400W SON-T or 250 or 400W HQL-T lamps. Aluminium housing and hinged diffuser frame and die cast aluminium mounting bracket, finished black. Lens in 5mm thick thermal – shock resistant tempered glass and reflector in high purity anodised aluminium. Designed for pole heights of 6-10m – as Whitecroft Lighting MISTRAL Q