



Optics

- Lamps:
 - 18W TC-D and 20W CDM-Tm
- Acrylic diffuser shade for soft ambient lighting effect with 18W TC-D lamp
- Reflector with 30° beam angle for accent lighting with 20W CMH Tm

Body

- Recessed multi-source downlighter with a brushed anodised aluminium body
- Electronic control gear included for 18W TC-D lamp
- Remote electronic gearbox required for each 20W CMH lamp
- To fit ceilings 5-25mm thickness



NOC Combi Double


Order Codes

NOC	HF Gear
NOC Combi Double	WACO490.04.4.20.2
NOC Combi Triple	WACO490.04.4.20.3
Remote Gear Box	GB-C20TME-P

Lamp Performance


Wattage	IL@25°C	Lamp Life
1 x 18W TC-DEL	1200	13,000hrs
1 x 20W CDM-Tm	1650	12,000hrs

Dimensions



Version	L	W	H	KG
Double	290	170	300	0.8
Triple	410	170	300	1.0

Photometric Performance



- 1 x 18W TC-D
- LOR = 67%
- SHR MAX = 1.81

	20W CDM-Tm	
	LUX	
M	20W	Ø
1.0m	3616	0.49
2.0m	904	0.98
3.0m	402	1.47
4.0m	180	2.10
	Medium 30°	

Utilisation Factors UF(F)

Room Reflectance	Room Index
C W F	1.00 3.00 5.00
0.70 0.50 0.20	0.43 0.68 0.81

To Specify

Recessed multi-source downlighter with a brushed anodised aluminium body and acrylic shade – as Whitecroft Lighting NOC