

NOC

multi-source downlighter

> weblink > **NOC**

Optics

- Lamps:
 - 18W TC-D and 20W CDM-Tm
- Acrylic diffuser shade for soft ambient lighting effect with 18W TC-D lamp
- Reflector with 30° beam angle for accent lighting with 20W CMH Tm

Body

- Recessed multi-source downlighter with a brushed anodised aluminium body
- Electronic control gear included for 18W TC-D lamp
- Remote electronic gearbox required for each 20W CMH lamp



NOC combi double


ORDER CODES

NOC	HF Gear
NOC Combi Double	WACO490.04.4.20.2
NOC Combi Triple	WACO490.04.4.20.3
Remote Gear Box	GB-C20TME-P

LAMP PERFORMANCE


Wattage	IL@25°C	Lamp Life
1 x 18W TC-DEL	1200	12,000hrs
1 x 20W CMH Tm	1650	12,000hrs

DIMENSIONS



Version	L	W	H	KG
Double	290	170	300	0.8
Triple	410	170	300	1.0

PHOTOMETRIC PERFORMANCE



- 1 x 18W TC-D
- LOR = 69%
- SHR MAX = 1.81

20W CDM-Tm

M	20W	Ø
1.0m	3616	0.49
2.0m	904	0.98
3.0m	402	1.47
4.0m	180	2.10

Medium 30°

Utilisation Factors UF(F)

Room Reflectance	Room Index
C W F	1.00 3.00 5.00
0.70 0.50 0.20	0.43 0.68 0.81

TO SPECIFY

Recessed multi-source downlighter with a brushed anodised aluminium body and acrylic shade – as Whitecroft Lighting NOC

