

oasis

direct/indirect architectural wall light

> weblink > **OAG**

Optics

- Lamp options:
 - 1 x 40W TC-L
 - 1 x 55W TC-L

Body

- Extruded aluminium body painted white
- Individual switch incorporated into bracket
- Specular wedge blade louvre positively retained via quick release springs
- Die cast aluminium end caps
- Asymmetric light distribution
- Upward light controlled by extruded acrylic lens



ORDER CODES

Oasis	HF Gear	3 hr Emergency
TC-L 1 x 40W	OAGW2H140	OAGW2H140EMIN
TC-L 1 x 55W	OAGW2H155	OAGW2H155EMIN


Options

DALI DIMMING	Replace H with Y in order code	i.e. OAGW2 Y 140
DSI DIMMING	Replace H with D in order code	i.e. OAGW2 D 140
SWITCH DIMMING	Replace H with X in order code	i.e. OAGW2 X 140
EASYTEST	Add suffix /ET to order code	i.e. OAGW2H140/ ET

LAMP PERFORMANCE


Wattage	IL@25°C	Lamp Life
1 x 40W TC-L	3500	20,000hrs
1 x 55W TC-L	4800	20,000hrs

DIMENSIONS



L	W	H	KG	KG
660	360	95	5.4	6.4

PHOTOMETRIC PERFORMANCE



- 1 x 55W TC-L
- LOR = 69.5%
 - SHR MAX = 2.16

Utilisation Factors UF(F)

Room Reflectance			Room Index		
C	W	F	1.00	3.00	5.00
0.70	0.50	0.20	0.39	0.56	0.60

TO SPECIFY

Wall mounted direct/indirect luminaire extruded aluminium body 95mm in depth acrylic lens for upward light component curved wedge louvre with asymmetric distribution – as Whitecroft Lighting OASIS