



Optics

- Lamp options:
 - 1 x 40W TC-L
 - 1 x 55W TC-L

Body

- Extruded aluminium body painted white
- Individual switch incorporated into bracket
- Specular wedge blade louvre positively retained via quick release springs
- Die cast aluminium end caps
- Asymmetric light distribution
- Upward light controlled by extruded acrylic lens




Order Codes

Oasis	HF Gear	3 hr Emergency
TC-L 1 x 40W	OAGW2H140	OAGW2H140EMIN
TC-L 1 x 55W	OAGW2H155	OAGW2H155EMIN

Options

DALI DIMMING	Replace H with Y	i.e. OAGW2Y140
SWITCH DIMMING	Replace H with X	i.e. OAGW2X140
EASYTEST	Add suffix /ET	i.e. OAGW2H140/ET
COMEPS	Add suffix /EP	i.e. OAGW2H140/EP

Photometric Performance



- 1 x 55W TC-L
- LOR = 69.5%
- SHR MAX = 2.16


Lamp Performance

Wattage	IL@25°C	Lamp Life
1 x 40W TC-L	3500	20,000hrs
1 x 55W TC-L	4800	20,000hrs

Utilisation Factors UF(F)

Room Reflectance	Room Index
C W F	1.00 3.00 5.00
0.70 0.50 0.20	0.39 0.56 0.60

Dimensions



L	W	H	KG	KG
660	360	95	5.4	6.4

To Specify

Wall mounted direct/indirect luminaire extruded aluminium body 95mm deep acrylic lens for upward light component curved wedge louvre with asymmetric distribution – as Whitecroft Lighting OASIS