




Edinburgh Airport

DIMENSIONS AND WEIGHT

LAMP WAYS	LONGITUDINAL DIMENSION A	WEIGHT KG
2 x 36W TC-L	493	5.7
2 x 40W TC-L	593	7.4
2 x 55W TC-L		



Cyra

ORDER CODES

COMPACT RECESSED ARCHITECTURAL FLUORESCENT

LUMINAIRE	LOUVRE	LAMP WAY	GEAR
CYRWH236	W2.500	2 x 36W TC-L	High frequency
CYRWH240	W2.1000	2 x 40W TC-L	
CYRWH255	W2.500	2 x 55W TC-L	

HIGH FREQUENCY REGULATING GEAR *Substitute R for H in part code*
R High frequency regulating gear i.e. CYRWR236

EMERGENCY *Add suffix to order codes above*
EMIN Integral emergency i.e. CYRWH236EMIN

EASYTEST OPTION *Add suffix to order codes above*
/ET  Integral self autotest i.e. CYRWH236EMIN/ET


To specify state:
Fully recessed compact fluorescent direct/indirect LG3 Cat 2 gull winged/louvred architectural luminaire, linear air handling slots – as Whitecroft Lighting CYRA.

Cyra

RECESSED 600 x 600 SEMI SPECULAR LG3 CAT 2
2 x 40W TC-L Lamps



- SHR MAX = 1.67
- DLOR = 0.43



UTILISATION FACTORS UF(F)		SHR NOM=1.50									
Room Reflectance	Room Index										
C	F	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.31	0.35	0.37	0.39	0.42	0.43	0.44	0.46	
0.50	0.30	0.20	0.28	0.32	0.34	0.36	0.39	0.40	0.41	0.43	
0.00	0.00	0.00	0.25	0.29	0.31	0.33	0.35	0.37	0.38	0.39	0.40

CONVERSION TERMS			
Lamp wattage	40W	55W	
UF and PC	1.00	0.93	