

Asymmetric Wallwasher

MOTIVATION

A recessed or surface mounted asymmetric wallwasher combining high performance with excellent vertical luminance uniformity within a space and low glare eliminating direct viewing of the lamp from normal viewing angles

APPLICATION

- Retail applications
- Shops
- Shelving
- Walls
- Displays to vertical surfaces

SPECIFICATION

- Lamps:
 - 1 x 55W TC-L
 - 2 x 55W TC-L
- Recessed or surface mount versions
- Recessed body – Exposed Tee 25mm or 15mm
- Body:
 - Fabricated steel
 - Polyester powder paint finish RAL9010 20% gloss
- BESA fixings on surface mount option
- High frequency gear as standard
- Fused terminal block
- Supplied less lamps

Louvre

- Reflector:
 - Lay-in asymmetric
 - Semi-specular, low glare
- Recommended spacing: 750mm from approximate vertical surface and on 1.8m centre for even illumination

Options

- Specular 'Power' reflector available dependent on quantity



ASYR155S



ASYU155S


DIMENSIONS AND WEIGHT

RECESSED LUMINAIRE	A	B	C
Single semi-specular reflector	594	75	225
Twin semi-specular reflector	1194	75	225

SURFACE LUMINAIRE	A	B	C	D	E
Single lamp	594	80	200	500	180
Twin lamp	1194	80	200	1100	180



Asymmetric Wallwasher
1 x 55W TC-L Compact Fluorescent Lamp



• DLOR = 0.535

Asymmetric Wallwasher

ORDER CODES

COMPACT FLUORESCENT WALLWASHER

RECESSED	LENGTH MM	LAMP WAY	GEAR	SURFACE
ASYR155S	600	1 x 55W TC-L	High frequency	ASYU155S
ASYR255S	1200	2 x 55W TC-L		ASYU255S

To specify state:

Fully recessed/surface compact fluorescent asymmetric luminaire. Semi specular parabolic low glare louvre – as Whitecroft Lighting ASYMMETRIC WALLWASHER.