

Ovolo

MOTIVATION


Classically simple but effective uplighting.

APPLICATION


- Feature lighting
- Conference rooms
- Board rooms
- Reception areas
- Domestic applications
- Corridors

SPECIFICATION

- Lamp options:
 - 1 x 18W TC-L
 - 2 x 18W TC-L
 - 1 x 24W TC-L
 - 2 x 24W TC-L
- Two part construction
- One piece pre-wired lamp and gear housing
- Natural stone texture glass fibre cover
- Two cover designs
- Cover suitable for over painting with ordinary emulsion
- Switchstart control gear
- High frequency option
- Supplied less lamps



CAS1200



CAS1400




CAS1500



DIMENSIONS

	W	H	D
CAS1200	425	247	212
CAS1400	490	195	195
CAS1500	510	200	250



Ovolo

ORDER CODES

INDIRECT WALL MOUNTED ARCHITECTURAL LIGHTING

CAS1200	CAS1400	CAS1500	SUPPLIED LESS LAMP	GEAR
CAS1200/118L	CAS1400/118L	CAS1500/118L	1 x 18W TC-L	switchstart
CAS1200/218L	CAS1400/218L	CAS1500/218L	2 x 18W TC-L	
CAS1200/124L	CAS1400/124L	CAS1500/124L	1 x 24W TC-L	
CAS1200/224L	CAS1400/224L	CAS1500/224L	2 x 24W TC-L	

GEAR OPTION Add suffix to order codes above

HF High frequency gear e.g. CAS1200/118LHF