

Sentry

MOTIVATION

To create a economic functional IP65 emergency bulkhead suitable for a wide variety of indoor and outdoor applications incorporating a simple plug-in gear tray assembly for rapid installation.

APPLICATION

- Wall or ceiling mounting (recess option)
- Exit routes
- Corridors
- Exit doors
- Canopies
- Walk ways
- Stairwells

SPECIFICATION

- Viewing distance up to 14m
- Low tack self adhesive legends – specify separately see page 117
- IP65 protection
- 3 hour maintained or non-maintained versions
- ABS body flame retardant
- 20mm side end and rear cable entry positions
- Rear terminal box entry
- Polycarbonate clear diffuser
- Simple ‘first fix’ housing
- Removable gear tray with plug and socket arrangement
- Fitted gasket
- Clip on diffuser
- Housing and diffuser meet 850°C hot wire test
- Recessing kit option
- Supplied with lamp
-  Integral self test version available see page 106



SEN/BH/NM/F8



Recessing kit



Sentry with low tack self adhesive Legend, see page 117 to order



FEATURES

	SEN/BH/NM/F8	SEN/BH/M/F8
MODE	Non-maintained	Maintained
DURATION	3 hours	3 hours
NORMAL LAMP OUTPUT	–	480lm
EMERGENCY LAMP OUTPUT	180lm	180lm
INPUT VOLTAGE	220/240V 50Hz	
RATING	8VA	20VA
BATTERY TYPE	High temperature Nickel Cadmium 24V 4Ah	
RECHARGE TIME	24 hours	24 hours

Sentry

ORDER CODES

EMERGENCY BULKHEAD

EMERGENCY UNIT	EMERGENCY LIGHTING	LAMP SUPPLIED
SEN / BH / NM / F8	3 hour non-maintained	1 x 8W T5
SEN / BH / M / F8	3 hour maintained	1 x 8W T5

EASYTEST OPTIONS Add suffix to order codes above

/ET  Integral self autotest

RECESSING KIT Order separately

SEN / RK Recessing kit

LOW TACK SELF ADHESIVE LEGENDS Order separately

See page 117 to specify

To specify state:

Surface/semi recessed 8W T5 3 hour maintained/non-maintained emergency bulkhead with 1st fix back and removable gear tray with plug and socket. Clip on diffuser, fitted gasket, IP65 – as Whitecroft Lighting SENTRY.