

Weatherproof

MOTIVATION

To design a exceptionally tough, economic and simple to install range of vandal resistant emergency fittings with an IP65 rating.

APPLICATION


- Exit doors – exterior
- Car parks
- Walk ways
- Leisure centres
- Schools
- Underground walkways

SPECIFICATION

- Viewing distance up to 22m
- Low tack self adhesive legends – specify separately see page 117
- IP65 protection
- 3 hour maintained or non-maintained versions
- ABS flame retardant body
- Side and end 20mm knockout conduit entries
- Side and rear terminal box entry
- Clear prismatic or opal polycarbonate diffuser
- Snap in white metal gear tray reflector
- Vandal resistant fixing screws
- Housing and diffuser meet 850°C hot wire test
- Recessing kit option
- Supplied with lamp
-  Integral self test version available see page 106



WBU/NM/3/1128



Recessing kit



FEATURES

	WBU/NM/3/1128	WBU/MA/3/1128
MODE	Non-maintained	Maintained
DURATION	3 hours	3 hours
NORMAL LAMP OUTPUT	–	480lm
EMERGENCY LAMP OUTPUT	180 m	180lm
INPUT VOLTAGE	220/240V 50Hz (other voltages available see order codes below)	
RATING	8VA	20VA
BATTERY TYPE	High temperature Nickel Cadmium 3.6V 4Ah	
RECHARGE TIME	24 hours	24 hours

Weatherproof

ORDER CODES

IP65 VANDAL RESISTANT EMERGENCY BULKHEAD

OPAL DIFFUSER	LAMP SUPPLIED	CLEAR PRISMATIC DIFFUSER
WBU/NM/3/1128	1 x 8W T5	WBC/NM/3/1128
WBU/MA/3/1128	1 x 8W T5	WBC/MA/3/1128

EASYTEST OPTION Add suffix to order codes above

/ET  Integral self autotest

RECESSING KIT Order separately

WBU/SRK Semi recessing kit

LOW TACK SELF ADHESIVE LEGENDS Order separately

See page 117 to specify

To specify state:
Surface/semi recessed 8W T5 3 hour maintained/non-maintained/emergency bulkhead. Clear prismatic/opal polycarbonate diffuser with vandal proof fixing screws. IP65 – as Whitecroft Lighting WEATHERPROOF.