

Exit

MOTIVATION

An unobtrusive versatile range of exit boxes with a slimline design one piece construction. Built in downlight aperture to highlight the door threshold.

APPLICATION


- Exit doors – interior
- Offices
- Hotels
- Wherever traditional exit signs are used

SPECIFICATION

- Viewing distances up to 36m
- Exit panels – specify separately, see page 117
- 3 hour maintained or non-maintained versions
- White powder coated steel housing
- 20mm conduit entries at each end of housing
- BESA box entry in rear
- Slide out legend panel to access internals
- Supplied with lamp
-  Integral self test version available see page 106



SEN/EX/NM/F8/AT with Legend panel, see page 117 to order



FEATURES

	SEN/EX/NM/F8	SEN/EX/M/F8
MODE	Non-maintained	Maintained
DURATION	3 hours	3 hours
NORMAL LAMP OUTPUT	–	480lm
EMERGENCY LAMP OUTPUT	180lm	180lm
INPUT VOLTAGE	220/240V 50Hz	220/240V 50Hz
RATING	8VA	20VA
BATTERY TYPE	High temperature Nickel Cadmium 24V 4Ah	
RECHARGE TIME	24 hours	24 hours

Exit

ORDER CODES

EMERGENCY EXIT SIGN

EMERGENCY UNIT	EMERGENCY LIGHTING	LAMP SUPPLIED
SEN/EX/NM/F8	3 hour non-maintained	1 x 8W T5
SEN/EX/M/F8	3 hour maintained	1 x 8W T5

EASYTEST OPTION Add suffix to order codes above

/ET  Integral self autotest

LEGEND PANELS Order separately

See page 117 to specify