

Egress Double

MOTIVATION

Ceiling mounting where viewing is required from both directions whilst maintaining the common design with Egress Mini and Maxi.

APPLICATION


- Ceiling mounting only
- Exit routes
- Corridor intersections
- T-Junctions
- Open plan areas
- Doorways

SPECIFICATION

- Viewing distance up to 36m
- Self adhesive legends – specify separately see page 117
- IP42 protection
- Maintained and non-maintained versions
- Slim profile
- BESA box mounting facility
- White body
- Snap in white metal gear tray reflector
- Housing and diffuser meet 850°C hot wire test
- Supplied with lamp
-  Integral self test version available see page 106



DSE/NM/3/1128W with self adhesive Legend see page 117 to order



FEATURES

	DSE/NM/3/1128/W	DSE/MA/3/1128/W
MODE	Non-maintained	Maintained
DURATION	3 hours	3 hours
NORMAL LAMP OUTPUT	–	480lm
EMERGENCY LAMP OUTPUT	180lm	180lm
INPUT VOLTAGE	220/240V 50Hz (other voltages available see order codes below)	
RATING	8VA	20VA
BATTERY TYPE	High temperature Nickel Cadmium 3.6V 4Ah	
RECHARGE TIME	24 hours	24 hours

Egress Double

ORDER CODES

DOUBLE SIDED EMERGENCY EXIT SIGN

EMERGENCY UNIT	EMERGENCY LIGHTING	LAMP SUPPLIED
DSE/NM/3/1128#	3 hour non-maintained	1 x 8W T5
DSE/MA/3/1128#	3 hour maintained	1 x 8W T5

EASYTEST OPTION Add suffix to order codes above

/ET  Integral self autotest

LEGEND PANELS Order separately

See page 117 to specify