




New Look
Bluewater




Ceiling retention
system



Finger grip
adjustment



Tilt stabilising
device



Die-cast
aluminium
housing




Compass® Jr.
downlighter
shown in
parked position

LAMP LIFE AND WEIGHT

	HOURS LIFE	KG
35W CDM-TC	9000	0.5
50W Low voltage	4000	0.5
50W Mains voltage	2000	0.5
35W Control gear box	2.0	

Luminaire weights exclude gear




Compass Jr.




CDM-TC




50W mains voltage



50W dichroic



35W CDM-TC
Gearbox supplied
complete



Electronic transformer
WEDT60
(specify separately)

Compass® Jr.

ORDER CODES

DIRECTIONAL DOWNLIGHTER

SPOT REFLECTOR CDM-T	LAMP SUPPLIED	BASE	COLOUR	FLOOD REFLECTOR
CDJ-TC35-11	35W CDM-TC 3000k	G8.5	Silver	CDJ-TC35-21
CDJ-TC35-12	35W CDM-TC 3000k		White	CDJ-TC35-22

50W DICHROIC LOW VOLTAGE

CDJ-T50M-11	50W 24°	GU5.3	Silver	—
CDJ-T50F-12	50W 24°		White	—

50W MAINS VOLTAGE

CDJ-P16-MD-1	50W 25° dichroic coating	GZ10	Silver	—
CDJ-P16-MD-2	50W 25° dichroic coating		White	—

TRANSFORMER OPTION

WEDT60	Whitecroft electronic transformer 60VA
--------	--

To specify state:

Recessed cast aluminium adjustable downlight. 35W CDM-TC/50W LV/50W PAR16 lamp. Bezel Ø <125mm recess depth <110mm. 340° rotation 0-60° tilt. Tilt stabilizer for firm angle set. Enclosed lamp holder, remote gear box with plug and socket connection – as Whitecroft Lighting COMPASS® JNR.