

Spotlights: Mains voltage track or surface mounted spotlight

Blade™ B100P

MOTIVATION

Designed for areas where a higher degree of punch is required the Blade™ B100P mains voltage spotlight accepts up to the 100W TH PAR 30 reflector lamps.

- APPLICATION**
- Retail**

 - Accent and display lighting
 - Feature lighting
 - Shop windows
 - Merchandising
 - Signage
- Commercial**

 - Feature areas
 - Receptions
 - Atriums
 - Foyers
 - Museums and galleries
 - Wallwashing

- SPECIFICATION**
- Lamps option:
 - 100W max
 - 100mm Ø PAR 30 tungsten halogen
 - Lamp base: E27
 - Body: Precision die cast aluminium
 - Finish: White
 - Suitable for dimming
 - Surface or track mounted
 - Track compatibility:
 - Whitecroft Direct M (mains voltage)
 - Concord® Lytespan® 1
 - Rotation: 350°
 - Head tilt: 180°
 - IP20 protection
 - F-mark compliance
 - Supplied without lamp
 - Special order versions available in black and silver – minimum order quantities apply



Blade™ B100P
100W PAR30


Angle 30°
FLOOD

HGT	LUX	Ø
1.0m	3500	0.54m
2.0m	875	1.07m
3.0m	390	1.61m
4.0m	220	2.14m

Blade™ B100P
100W PAR30

Angle 10°
SPOT

HGT	LUX	Ø
1.0m	10000	0.18m
2.0m	2500	0.35m
3.0m	1110	0.53m
4.0m	625	0.70m



Blade™ B100P

ORDER CODES

MAINS VOLTAGE TRACK OR SURFACE MOUNTED SPOTLIGHT

VERSION	MOUNTING	SUPPLIED LESS LAMP
B100P-MTW	Whitecroft Direct M	PAR 30 100W
B100P-CTW	Concord® Lytespan® 1	Tungsten halogen lamp
B100P-MSW	Surface mounted	

To specify state:
Surface/track mounted low voltage spotlight. Die cast aluminium construction with 350° rotation and 180° tilt. Spotlight head to protrude <200mm from ceiling line – as Whitecroft Lighting BLADE™ B100P.