

Spotlights: Mains voltage track or surface mounted spotlight

Blade™ B65P

MOTIVATION


Designed for areas where a higher degree of punch is required the Blade™ B65P mains voltage spotlights accepts up to the 50W TH PAR 20 reflector lamps.

APPLICATION

- Retail**
 - Accent and display lighting
 - Feature lighting
 - Shop windows
 - Merchandising
 - Signage
- Commercial**
 - Feature areas
 - Receptions
 - Atriums
 - Foyers
 - Museums and galleries
 - Wallwashing

SPECIFICATION

- Lamp options:
 - 50W max
 - 65mm Ø PAR 20 tungsten halogen
- Lamp base: E27
- Body: Precision die cast aluminium
- Finish: White
- Suitable for dimming
- Surface or track mounted
- Track compatibility:
 - Whitecroft Direct M (mains voltage)
 - Concord® Lytespan® 1
- Rotation: 350°
- Head tilt: 180°
- IP20 protection
- F-mark compliance
- Supplied without lamp
- Special order versions available in black and silver – minimum order quantities apply



Blade™ B65P

ORDER CODES

MAINS VOLTAGE TRACK OR SURFACE MOUNTED SPOTLIGHT

VERSION	MOUNTING	SUPPLIED LESS LAMP
B65P-MTW	Whitecroft Direct M	PAR 20 65mm Tungsten halogen lamp*
B65P-CTW	Concord® Lytespan® 1	
B65P-MSW	Surface mounted	

* 50W maximum

To specify state:
Surface/track mounted mains voltage spotlight suitable for PAR 20 tungsten halogen dichroic reflector lamp. Die cast aluminium construction with 350° rotation and 180° tilt. To protrude <199mm from ceiling line – as Whitecroft Lighting BLADE™ B65P.