


Power connector  
DT-LPCS2



White surface mounting  
brackets DT-LSM2



Rod suspension  
500mm DT-LRS052



Flexible coupler  
DT-LPFC2



150VA Surface  
mounted transformer  
DT-SMT1502




Ceiling plate outlet  
DT-LCPO3





Black surface mounting  
brackets DT-LSM3



Wire suspension  
DT-LWS3



Pre-wired power feed  
DT-LPFO5-1053



## Direct L Track System

### ORDER CODES

LOW VOLTAGE 25A LOW PROFILE SINGLE CIRCUIT TRACK SYSTEM

#### STANDARD WHITE KIT

|            |                                                                                                                                                       |            |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| DT-L1200K2 | 1200mm 12V 25A single circuit track kit including:-<br>– 3 x surface suspension brackets<br>– 1 x power feed with a 500mm transformer connection lead | DT-L1200K3 |
| DT-L2000K2 | 2000mm 12V 25A single circuit track kit including:-<br>– 4 x surface suspension brackets<br>– 1 x power feed with a 500mm transformer connection lead | DT-L2000K3 |

#### STANDARD BLACK KIT

#### WHITE TRACK

DT-L3000T2 3000mm length of track

#### BLACK TRACK

DT-L3000T3

Can easily be cut to specific length on site. Direct L requires a suspension fixing every 600mm.

#### WHITE MOUNTING OPTIONS

|           |                                     |           |
|-----------|-------------------------------------|-----------|
| DT-LSM2   | Surface mounting brackets, set of 2 | DT-LSM3   |
| DT-LFS2   | Floating suspension 60mm,           | DT-LFS3   |
| DT-LRS052 | Rod suspension 500mm                | DT-LRS053 |
| DT-LRS202 | Rod suspension 1500mm               | DT-LRS203 |
| DT-LWS2   | Wire suspension 2000mm              | DT-LWS3   |

#### BLACK MOUNTING OPTIONS

The track design includes a dovetail feature for fixing to a variety of mounting devices.

#### WHITE PRE-WIRED POWER FEEDS

|               |                                                                    |               |
|---------------|--------------------------------------------------------------------|---------------|
| DT-LPF05-1052 | Prewired power feed, 500mm cable 1.5mm <sup>2</sup> , (105VA max.) | DT-LPF05-1053 |
| DT-LPF05-3002 | Prewired power feed, 500mm cable 6.0mm <sup>2</sup> (300VA max.)   | DT-LPF05-3003 |
| DT-LPF25-3002 | Prewired power feed, 2500mm cable 6.0mm <sup>2</sup> (300VA max.)  | DT-LPF25-3003 |

#### BLACK PRE-WIRED POWER FEEDS

The low voltage power feed can be fitted anywhere along the length of track for convenient connection to the transformer. Power feeds are only available pre-wired to ensure connectivity.

#### WHITE COUPLERS

|          |                                      |          |
|----------|--------------------------------------|----------|
| DT-LPFC2 | 12V track power flexible coupler     | DT-LPFC3 |
| DT-LPSC2 | 12V track power straight coupler     | DT-LPSC3 |
| DT-LIFC2 | 12V track isolating flexible coupler | DT-LIFC3 |
| DT-LISC2 | 12V track isolating straight coupler | DT-LISC3 |

#### BLACK COUPLERS

Couplers can be used to insulate sections of track or pass power from one piece of track to another depending on the type specified.

#### WHITE ACCESSORIES

|          |                                           |          |
|----------|-------------------------------------------|----------|
| DT-LPCS2 | Power connector cover, shallow            | DT-LPCS3 |
| DT-LPCD2 | Power connector cover, deep               | DT-LPCD3 |
| DT-LCPO2 | Ceiling plate outlet, white, cut out 55mm | DT-LCPO3 |

#### BLACK ACCESSORIES

A selection of covers are available to add the finishing touch to the installation.

#### WHITE SURFACE MOUNTED TRANSFORMERS

|            |                                   |            |
|------------|-----------------------------------|------------|
| DT-SMT1502 | 150VA surface mounted transformer | DT-SMT1503 |
| DT-SMT3002 | 300VA surface mounted transformer | DT-SMT3003 |

#### BLACK SURFACE MOUNTED TRANSFORMERS

Weight 150VA - 2.5kg 300VA - 4.1kg

Low profile toroidal transformer mounted into an attractive casing. Protection device of automatic switch off in case of overload, replaceable fuse for short circuit protection.

Remote single fuse transformers for track. See TXS on page 174.