

Direct M *Track System*

MOTIVATION

Direct M track is manufactured from extruded aluminium with a maximum rating of 16 amps from a 240V mains supply. Available as standard kits including 1200 or 2000mm track lengths and appropriate fixings, or as individual system components, the Direct M track is designed for use with Whitecroft's range of mains voltage spotlights and projectors.

APPLICATION

Retail

- Accent and display lighting
- Feature lighting
- Shop windows
- Merchandising

Commercial

- Feature areas
- Receptions
- Atriums
- Foyers
- Museums and galleries
- Wallwashing

SPECIFICATION

- 1200 or 2000mm track lengths, 28mm Ø
- 240V 16A single circuit
- White or black
- Surface suspension brackets
- End track power feed
- Flexible power coupler



Torque p158-161



Saturn p162



Blade™ B100P p167




Blade™ B50T p164





Mains track power feed DT-MPF2



Surface mounted brackets DT-MSM3



Mains track power flexible coupler DT-MPFC2



Direct M Track System

ORDER CODES

MAINS VOLTAGE 16A LOW PROFILE SINGLE CIRCUIT TRACK SYSTEM

WHITE DIRECT M		BLACK DIRECT M
DT-M1200K2	1200mm 240V 16A single circuit track kit including three surface suspension brackets and an end power feed	DT-M1200K3
DT-M2000K2	2000mm 240V 16A single circuit track kit including four surface suspension brackets and an end power feed	DT-M2000K3

SYSTEM COMPONENTS		
DT-M30002	3000mm length of track (Can easily be cut to specific lengths on site)	DT-M30003
DT-MSM2	Surface mounted brackets, set of 2	DT-MSM3
DT-MPF2	Mains track end power feed	DT-MPF3
DT-MPFC2	Mains track power flexible coupler	DT-MPFC3