

Transformers, Powerpack &

SPECIFICATION

WEDT Electronic transformer

- Lightweight design developed for easy installation
- Loop-in loop-out primary connections
- Excellent voltage regulation
- Dual stage transient protection
- Through hole installation or surface mount
- Fully dimmable using standard resistive load dimmers



TD toroidal transformers

TDB Transformers

- Reliable, dedicated one-to-one budget toroidal transformers
- Flex leaded single output
- Flame retardant polycarbonate case sealed to IP65
- Resettable fuse device
- Fully dimmable using standard inductive load dimmers


TDM Transformers

- Maintenance free toroidal transformers for multi-lamp control ideal for applications where the mounting position is likely to be normally inaccessible
- Flame retardant polycarbonate cover
- Auto-reset thermal cut out primary protection
- Resettable fuse device on each individual output



WET Weatherproof transformer

- Enclosure to IP56
- Grey ABS moulded housing
- Quick release lid fasteners
- 4 screw fixings outside gasket area
- Supplied with 2 IP67 PG16 nylon cable glands
- 8 further knockouts
- 240/230V input 11.4V output
- Primary fuse and terminal cut out
- 3 way screw terminal mains connection



Transformers

ORDER CODES

TRANSFORMERS FOR LOW VOLTAGE DOWNLIGHTS AND SPOTLIGHTS

WEDT	MAXIMUM NO. OF LAMPS			NO. OF TERMINALS	DEPTH MM	HEIGHT MM	WIDTH MM	WEIGHT KG
	20W	35W	50W					
WEDT60	3	2	1	1	150	35	42	0.20
WEDT105	5	3	2	1	150	35	42	0.20

TDB

TDB020W	1	-	-	1	63	78		0.66
TDB035W	-	1	-	1	63	78		0.66
TDB050W	-	-	1	1	63	78		0.68

TDM

TDM100W	4	2	2	2	110	106	110	1.90
TDM150W	6	3	3	3	110	106	110	2.20
TDM200W	8	5	4	4	110	106	110	2.48
TDM250W	10	5	5	5	138	130	138	4.00
TDM300W	12	6	6	6	138	130	138	4.10

WET (WEATHERPROOF ENCLOSURE TO IP56)

				A	B	C
WET/50VA	2	1	1	124	124	100
WET/100VA	4	2	2	175	124	100
WET/150VA	6	3	3	175	124	100
WET/200VA	8	5	4	175	175	100
WET/250VA	10	5	5	175	175	100
WET/300VA	12	6	6	175	175	126

SINGLE FUSE TRANSFORMERS FOR TRACK

TXS301T	15	8	6	1	222	92	112	3.0
TXS602T	30	17	12	2	295	150	155	7.0