




Other mounting options and colours available quantities permitting, as shown above


WEIGHT, WINDAGE AND MEASUREMENTS

SINGLE SPOKE	WATTAGE	WEIGHT	WINDAGE	MEASUREMENTS	
	W	KG	M ²	A Ø	B
	70W	14.5	0.09	473	343
	150W	15.3			
	250W	27.0	0.14	635	502
	400W	28.3			
TWIN SPOKE					
	70W	28.0	0.16	473	343
	150W	29.1			
	250W	52.0	0.27	635	502
	400W	54.6			



Magnudisc

ORDER CODES
LIGHTING FOR OPEN SPACES

DS VERSION 473 Ø	LAMP SUPPLIED	MOUNTING	LAMP SUPPLIED	DM VERSION 635 Ø
DSDF70S1P	70W SON-T	 Single spoke	250W SON-T	DMDF250S1P
DSDF150S1P	150W SON-T		400W SON-T	DMDF400S1P
DSDF70S1T	70W SON-T		250W SON-T	DMDF250S1T
DSDF150S1T	150W SON-T		400W SON-T	DMDF400S1T
DSDF70H1P	70W HQI-T		250W HQI-T	DMDF250H1P
DSDF150H1P	150W HQI-T		400W HQI-T	DMDF400H1P
DSDF70H1T	70W HQI-T		250W HQI-T	DMDF250H1T
DSDF150H1T	150W HQI-T		400W HQI-T	DMDF400H1T
DSDG70S1P	70W SON-T	 Twin spoke	250W SON-T	DMDG250S1P
DSDG150S1P	150W SON-T		400W SON-T	DMDG400S1P
DSDG70S1T	70W SON-T		250W SON-T	DMDG250S1T
DSDG150S1T	150W SON-T		400W SON-T	DMDG400S1T
DSDG70H1P	70W HQI-T		250W HQI-T	DMDG250H1P
DSDG150H1P	150W HQI-T		400W HQI-T	DMDG400H1P
DSDG70H1T	70W HQI-T		250W HQI-T	DMDG250H1T
DSDG150H1T	150W HQI-T		400W HQI-T	DMDG400H1T
DSDK70S1P	70W SON-T	 Wall mounted	250W SON-T	DMDK250S1P
DSDK150S1P	150W SON-T		400W SON-T	DMDK400S1P
DSDK70S1T	70W SON-T		250W SON-T	DMDK250S1T
DSDK150S1T	150W SON-T		400W SON-T	DMDK400S1T
DSDK70H1P	70W HQI-T		250W HQI-T	DMDK250H1P
DSDK150H1P	150W HQI-T		400W HQI-T	DMDK400H1P
DSDK70H1T	70W HQI-T		250W HQI-T	DMDK250H1T
DSDK150H1T	150W HQI-T		400W HQI-T	DMDK400H1T

COLOURS Add suffix to order codes above

- 22 Black housing/black spoke i.e. DSDF70S1P22
- 42 White housing/black spoke i.e. DSDF70S1P42
- 44 White housing/white spoke i.e. DSDF70S1P44

MOUNTING ACCESSORIES Replace ## with column Ø (mm), see pages 231-233

DS/SPGA / ##	Post top adaptor	DM /SPGA / ## / 60
--------------	------------------	--------------------

To specify state:
Amenity luminaire with aluminium housing 70/150/250/400W SON/HQI lamp, T/P distribution, tiltable head and hinged removable gear tray – IP55 as Whitcroft Lighting MAGNUDISC.

DISTRIBUTION PATTERNS

