

Type 2

MOTIVATION

The Type 2 has been designed to London Underground standards. With a unique aerofoil shape that accommodates optics for two distribution patterns. The asymmetric reflector throws light forward and a wallwasher version is used for lighting signage and advertising hoardings.

APPLICATION

- Tube stations
- Platform lighting
- Ticket halls
- Concourse areas
- Walkways
- Signage
- Main line stations

SPECIFICATION

- London Underground Ltd. (LUL) approved
- Designed for 40 year life span
- Lamp options and distribution patterns:
 - Type 2A
1 x 58W T8 wallwash
 - Type 2B
1 x 58W T8 Asymmetric
 - Type 2C
2 x 36W TC-L wallwash
 - Type 2D
2 x 36W TC-L asymmetric
 - Type 2E
2 x 55W TC-L wallwash
 - Type 2F
2 x 55W TC-L asymmetric
- IP65 construction
- Body:
 - Extruded aluminium body
 - Cast aluminium end caps
- Door:
 - Extruded aluminium sides
 - Cast aluminium ends
 - Hinged and glazed with toughened safety glass
- Wedge blade louvre fixed to door
- Access via 4 quarter turn fasteners
- High frequency control gear
- Specify cable entry requirements
- Paint finish RAL9007 silver
- Non toxic fume emitting paint
- Mounting: Special bracket (specify separately)
- Weight 18.5kg (58W version less mounting brackets)
- Supplied with lamps



Type 2



Access via hinged door



5° locking design feature allows accurate continuous mounting



Cast aluminium mounting bracket