



Lamps



12V HALOGEN CAPSULE					
Mains Current (A)	Wattage	Ø	Length	Cap	NL
0.09	20W	12	44	GY6.35	350
0.15	35W	12	44	GY6.35	630
0.22	50W	12	44	GY6.35	975
0.33	75W	12	44	GY6.35	1600
0.44	100W	12	44	GY6.35	2400
Colour temperature – 3000°K		Ra 100			

Lamp life: 3000 hours
Lumen maintenance: 0.98




BI-PIN ENCLOSED DICHOIC REFLECTOR						
Mains Current (A)	Wattage	Ø	M ref	Beam type	Beam Angle	Peak CD
0.09	20W	50	M368	Flood	12°	5000
0.09	20W	50	M394	Flood-med	24°	1600
0.09	20W	50	M369	Flood-wide	38°	790
0.15	35W	50	M376	Flood	12°	9000
0.15	35W	50	M370	Flood-med	24°	3000
0.15	35W	50	M381	Flood-wide	38°	1450
0.22	50W	50	M376	Flood	12°	12500
0.22	50W	50	M370	Flood-med	24°	4200
0.22	50W	50	M381	Flood-wide	38°	2250
0.22	50W	50	M280	Flood-v.wide	60°	950
Colour temperature – 3000°K		Ra 100				

Lamp life: 3000 hours
Lumen maintenance: 0.98



240V HALOGEN					
Mains Current (A)	Wattage	Ø	Length	Cap	IL
0.31	75W	32	105	E27	1000
0.42	100W	32	105	E27	1350
0.63	150W	32	105	E27	2400
1.04	250W	32	105	E27	4000
Colour temperature – 3000°K		Ra 100			

Lamp life: 2000 hours
Lumen maintenance: 0.98



240V HALOGEN REFLECTOR PAR						
Mains Current (A)	Wattage	Ø	Length	Cap	Beam Angle	Peak CD
PAR 20						
0.21	50W	63	85	E27	10°	3000
0.21	50W	63	85	E27	25°	1000
PAR 30						
0.31	75W	97	91	E27	10°	6900
0.31	75W	97	91	E27	30°	2200
0.41	100W	97	91	E27	10°	10000
0.41	100W	97	91	E27	30°	3500
Colour temperature – 2900°K		Ra 100				

Lamp life: 2500 hours
Lumen maintenance: 0.98