



Photometry

Comfort Surface

SPECULAR LG3 CAT 2.200 LOUVRE
1 x 58W T8 Lamp



- SHR MAX = 1.70
- DLOR = 0.559




UTILISATION FACTORS UF(F)		SHR NOM=1.50									
Room Reflectance		Room Index									
C	W	F	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.40	0.45	0.49	0.51	0.54	0.56	0.58	0.59	0.60
0.50	0.30	0.20	0.36	0.41	0.45	0.47	0.51	0.53	0.54	0.56	0.57
0.00	0.00	0.00	0.32	0.37	0.41	0.43	0.46	0.48	0.49	0.51	0.52

CONVERSION TERMS


Lamp Length	1.2m	1.5m
Lamp wattage	36W	58W
UF and PC	0.98	1.00

Comfort Surface

SPECULAR LG3 CAT 2.200 LOUVRE
2 x 58W T8 Lamps



- SHR MAX = 1.61
- DLOR = 0.571



UTILISATION FACTORS UF(F)		SHR NOM=1.50									
Room Reflectance		Room Index									
C	W	F	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.41	0.46	0.50	0.52	0.56	0.58	0.59	0.61	0.62
0.50	0.30	0.20	0.37	0.42	0.46	0.48	0.52	0.54	0.55	0.57	0.58
0.00	0.00	0.00	0.33	0.38	0.42	0.44	0.47	0.49	0.50	0.52	0.53

CONVERSION TERMS


Lamp Length	1.2m	1.5m
Lamp wattage	36W	58W
UF and PC	0.98	1.00

Classic II

SURFACE LUMINAIRE
Acrylic Diffuser 1 x 1200mm 36W T8 Lamp



- SHR MAX = 1.65
- DLOR = 0.522



UTILISATION FACTORS UF(F)		SHR NOM=1.50									
Room Reflectance		Room Index									
C	W	F	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.34	0.38	0.43	0.46	0.50	0.53	0.55	0.58	0.60
0.50	0.30	0.20	0.27	0.31	0.35	0.38	0.42	0.45	0.47	0.50	0.52
0.00	0.00	0.00	0.21	0.24	0.27	0.29	0.32	0.34	0.36	0.39	0.41

CONVERSION TERMS


Lamp Length	0.6m	1.2m	1.5m	1.8m
Lamp wattage	18W	36W	58W	70W
UF and PC	0.99	1.0	1.01	1.01

Classic II

SURFACE LUMINAIRE
Acrylic Diffuser 2 x 1200mm 36W T8 Lamps



- SHR MAX = 1.61
- DLOR = 0.497




UTILISATION FACTORS UF(F)		SHR NOM=1.50									
Room Reflectance		Room Index									
C	W	F	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.32	0.37	0.41	0.44	0.48	0.51	0.53	0.56	0.57
0.50	0.30	0.20	0.26	0.30	0.34	0.37	0.41	0.43	0.45	0.48	0.50
0.00	0.00	0.00	0.20	0.23	0.26	0.28	0.31	0.33	0.35	0.37	0.39

CONVERSION TERMS

Lamp Length	0.6m	1.2m	1.5m	1.8m
Lamp wattage	18W	36W	58W	70W
UF and PC	0.98	1.0	1.01	1.01


Cornice

LINEAR SURFACE 1 x 1200mm OPAL DIFFUSER
36W Lamp



Cornice

LINEAR SURFACE 1 x 1200mm PRISMATIC DIFFUSER
36W Lamp




Stiletto

ENCLOSED SURFACE LUMINAIRE
Acrylic Diffuser 1 x 1200mm 36W T8 Lamp



- SHR MAX = 1.65
- DLOR = 0.522



UTILISATION FACTORS UF(F)		SHR NOM=1.50									
Room Reflectance		Room Index									
C	W	F	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.34	0.38	0.43	0.46	0.50	0.53	0.55	0.58	0.60
0.50	0.30	0.20	0.27	0.31	0.35	0.38	0.42	0.45	0.47	0.50	0.52
0.00	0.00	0.00	0.21	0.24	0.27	0.29	0.32	0.34	0.36	0.39	0.41

CONVERSION TERMS


Lamp Length	0.6m	1.2m	1.5m	1.8m
Lamp wattage	18W	36W	58W	70W
UF and PC	0.99	1.0	1.01	1.01

Stiletto

ENCLOSED SURFACE LUMINAIRE
Acrylic Diffuser 2 x 1200mm 36W T8 Lamps



- SHR MAX = 1.61
- DLOR = 0.497



UTILISATION FACTORS UF(F)		SHR NOM=1.50									
Room Reflectance		Room Index									
C	W	F	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.32	0.37	0.41	0.44	0.48	0.51	0.53	0.56	0.57
0.50	0.30	0.20	0.26	0.30	0.34	0.37	0.41	0.43	0.45	0.48	0.50
0.00	0.00	0.00	0.20	0.23	0.26	0.28	0.31	0.33	0.35	0.37	0.39

CONVERSION TERMS


Lamp Length	0.6m	1.2m	1.5m	1.8m
Lamp wattage	18W	36W	58W	70W
UF and PC	0.98	1.0	1.01	1.01

Rapier

ENCLOSED SURFACE LUMINAIRE
Acrylic Diffuser 1 x 1200mm 36W Lamp



- SHR MAX = 1.7
- DLOR = 0.621
- ULOR = 0.118



UTILISATION FACTORS UF(F)		SHR NOM=1.50									
Room Reflectance		Room Index									
C	W	F	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.39	0.44	0.49	0.53	0.58	0.61	0.64	0.67	0.69
0.50	0.30	0.20	0.32	0.37	0.41	0.45	0.49	0.53	0.55	0.59	0.62
0.00	0.00	0.00	0.24	0.28	0.32	0.35	0.39	0.42	0.44	0.47	0.49

CONVERSION TERMS

Lamp Length	1.2m	1.5m	1.8m
Lamp wattage	36W	58W	70W
UF and PC	1.0	1.02	1.02