


Photometry


20W DICHROIC Angle 12°
12V 50mm Ø

HGT	LUX	Ø
1.0m	4000	21cm
2.0m	1000	42cm
3.0m	450	64cm




20W DICHROIC Angle 36°
12V 50mm Ø

HGT	LUX	Ø
1.0m	800	65cm
1.5m	360	97cm
2.0m	200	130cm




35W DICHROIC Angle 18°
12V 50mm Ø

HGT	LUX	Ø
1.0m	3400	31cm
2.0m	850	63cm
3.0m	380	95cm




35W DICHROIC Angle 38°
12V 50mm Ø

HGT	LUX	Ø
1.0m	1450	68cm
1.5m	650	103cm
2.0m	360	137cm





50W DICHROIC Angle 12°
12V 50mm Ø

HGT	LUX	Ø
1.0m	11000	21cm
2.0m	2750	42cm
3.0m	1220	64cm
4.0m	690	85cm




50W DICHROIC Angle 24°
12V 50mm Ø

HGT	LUX	Ø
1.0m	4200	45cm
1.5m	1870	67cm
2.0m	1050	90cm




50W DICHROIC Angle 30°
12V 50mm Ø

HGT	LUX	Ø
1.0m	3400	54cm
1.5m	2270	80cm
2.0m	850	107cm




50W DICHROIC Angle 38°
12V 50mm Ø

HGT	LUX	Ø
1.0m	2250	68cm
1.5m	1000	103cm
2.0m	560	137cm



50W DICHROIC Angle 60°
12V 50mm Ø

HGT	LUX	Ø
0.5m	3800	57cm
1.0m	950	115cm
1.5m	420	137cm



Downlight/Spotlight: LDR and HiWire
Pendant: Ice