

Mirage MD24 Cat 2 compact downlighter

SPACING					
LUMEN PACKAGE	CEILING HEIGHT (M)	TRANSVERSE TO WALL	TRANSVERSE SPACING	AXIAL TO WALL	AXIAL SPACING
Escape routes 1 lux minimum along centre line					
150	2.7	3.0	7.6	3.0	7.0
150	3.0	3.0	8.0	3.0	7.0
Anti-panic open areas 0.5 lux minimum arranged in a regular array					
150	2.7	3.6	7.5	3.0	6.3
150	3.0	3.6	8.1	3.2	6.9

Trimpak Batten C/W reflector

SPACING					
LUMEN PACKAGE	CEILING HEIGHT (M)	TRANSVERSE TO WALL	TRANSVERSE SPACING	AXIAL TO WALL	AXIAL SPACING
Escape routes 1 lux minimum along centre line					
300	3.0	4.1	10.1	3.7	9.3
300	4.0	4.2	11.0	3.9	10.1
Anti-panic open areas 0.5 lux minimum arranged in a regular array					
300	3.0	4.3	10.0	4.1	9.0
300	4.0	4.5	12.0	4.3	11.0

Horizon Surface compact downlighter

SPACING					
LUMEN PACKAGE	CEILING HEIGHT (M)	TRANSVERSE TO WALL	TRANSVERSE SPACING	AXIAL TO WALL	AXIAL SPACING
Escape routes 1 lux minimum along centre line					
200	2.7	2.4	6.4	2.4	6.4
200	3.0	2.3	6.4	2.3	6.4
Anti-panic open areas 0.5 lux minimum arranged in a regular array					
200	2.7	2.8	7.0	2.8	7.0
200	3.0	3.0	7.2	3.0	7.2

ACFD Weatherproof industrial

SPACING					
LUMEN PACKAGE	CEILING HEIGHT (M)	TRANSVERSE TO WALL	TRANSVERSE SPACING	AXIAL TO WALL	AXIAL SPACING
Escape routes 1 lux minimum along centre line					
300	3.0	3.5	9.0	2.9	7.5
300	4.0	3.3	9.4	2.7	7.8
Anti-panic open areas 0.5 lux minimum arranged in a regular array					
300	3.0	3.8	10.1	3.6	8.7
300	4.0	3.9	10.5	3.8	9.0

Trimpak Batten C/W polycarbonate diffuser

SPACING					
LUMEN PACKAGE	CEILING HEIGHT (M)	TRANSVERSE TO WALL	TRANSVERSE SPACING	AXIAL TO WALL	AXIAL SPACING
Escape routes 1 lux minimum along centre line					
300	3.0	3.0	7.5	2.8	6.8
Anti-panic open areas 0.5 lux minimum arranged in a regular array					
300	3.0	3.5	8.3	3.3	7.8

Sentry Weatherproof bulkhead

SPACING					
LUMEN PACKAGE	CEILING HEIGHT (M)	TRANSVERSE TO WALL	TRANSVERSE SPACING	AXIAL TO WALL	AXIAL SPACING
Escape routes 1 lux minimum along centre line					
180	2.0	1.9	6.5	1.5	4.4
180	2.5	1.4	6.0	1.3	4.3
180	3.0	0.8	4.9	0.8	4.1
Anti-panic open areas 0.5 lux minimum arranged in a regular array					
180	2.0	2.8	7.9	2.0	4.6
180	2.5	2.6	8.4	2.0	5.2
180	3.0	2.2	8.8	2.0	5.4

* Including 0.5m border area