

Pathfinder 2 Bulkhead IP65 Decorative



Decorative surface LED bulkhead for 24V DC Pathfinder 2
central battery system



Decorative surface bulkhead
Exit

Optics

- Dedicated LED emergency bulkhead for Pathfinder 2 system
- Open area lighting distributions
- Maintained as standard
- Can be configured as switched maintained, dimmed or non-maintained
- Robust, compact and low energy solution

Body

- Injection moulded polycarbonate housing
- Clear polycarbonate diffuser with fresnel lens
- IP65 rated
- Surface mounted convex design in white finish
- Input voltage 24V DC
- Supplied complete with driver
- 1W total power, 100mA output current
- Bulkhead and Exit sign housing versions
- Exit sign version requires legend panel, supplied separately
- Legends supplied in accordance with BS 5266-1 (ISO7010)
- Legends have a viewing distance of up to 20m

Note: Pathfinder 2 LED luminaires can only be used as part of a Pathfinder 2 system

Order codes

Description	Order Code
Bulkhead only	PFD2CONV
Exit Bulkhead	PFD2CONVEXIT
Exit version requires legend panel, ordered separately	

Legend panels for Exit version

Description	Order Code
Double sided legend panel 'up' arrow	PFD2CONVEXIT/DU
Double sided legend panel 'down' arrow	PFD2CONVEXIT/DD
Double sided legend panel 'left-right' arrow	PFD2CONVEXIT/DLR

Dimensions

VERSION	L	W	H	KG(EM)
Bulkhead	240	130	50	1.0
Exit version	240	130	100	1.4

To Specify

Dedicated IP65 rated LED decorative surface emergency bulkhead / exit sign for 24V DC central battery, central test emergency lighting system. Fully addressable emergency lighting points. Control unit with programmable interface – as Whitecroft Lighting PATHFINDER 2
