

Pathfinder 2 Bulkhead IP65 Surface



Surface IP65 LED bulkhead for 24V DC Pathfinder 2 central battery system



Optics

- Dedicated LED emergency bulkhead for Pathfinder 2 system
- Open area lighting distributions
- Maintained as standard
- Can be configured as switched maintained, dimmed or non-maintained
- Robust, compact and low energy solution

Body

- Injection moulded polycarbonate housing
- Clear polycarbonate diffuser with fresnel lens
- IP65 rated with IK10 impact protection
- Surface mounted in white finish
- Input voltage 24V DC
- Supplied complete with driver
- 1W total power, 100mA output current
- Optional self-adhesive legend kit with a choice of arrow direction
- Legends supplied in accordance with BS 5266-1 (ISO7010)
- Legends have a viewing distance of up to 21m

Note: Pathfinder 2 LED luminaires can only be used as part of a Pathfinder 2 system

Order codes

Description	Order Code
Surface IP65	PFD2EX65

Accessories

Self Adhesive Legend Kit	EX65LK/7010

Dimensions

VERSION	L	W	H	KG(EM)
Surface IP65	350	120	90	1.2

To Specify

Dedicated IP65 rated LED surface emergency bulkhead for 24V DC central battery, central test emergency lighting system. Fully addressable emergency lighting points. Control unit with programmable interface – as Whitecroft Lighting PATHFINDER 2