

Pathfinder 2 Twinspot

Surface emergency twinspot for 24V DC Pathfinder 2 central battery system



Optics

- Dedicated LED emergency twinspot for Pathfinder 2 system
- 2 adjustable heads with medium beam distribution
- 5000K LEDs
- Maintained as standard
- Can be configured as switched maintained, dimmed or non-maintained
- Robust, compact and low energy solution

Body


- IP40
- Polycarbonate diffuser on each head
- Injection moulded polycarbonate body
- White finish RAL 9010
- Wall mounted
- 20mm knockout for cable entry in side of body
- Rotation between 45-90° down and 20-90° side (see installation leaflet)
- Supplied complete with driver
- 3.7W total power, 605mA output current

Note: Pathfinder 2 LED luminaires can only be used as part of a Pathfinder 2 system

Order codes


Description	Order Code	L70B50	L80B50	L90B50
Twinspot	PFD2TSL2NM	>100K	>100K	55K

Dimensions



VERSION	L	W	H	H1	KG(EM)
Twinspot	275	50	300	155	3.6

Photometric Performance



5000K, 380 lumens
LOR = 100%

To Specify

Surface mounted emergency luminaire with injection moulded polycarbonate housing. Two piece body for ease of installation, with two independently adjustable heads. For 24V DC central battery, central test emergency lighting system. Fully addressable emergency lighting points. Control unit with programmable interface – as Whitecroft Lighting PATHFINDER 2