

Optics

- High performance, high output LED emergency luminaires supplied complete with driver
- Only for use with emergency Pathfinder system
- Specifically designed for application in areas that require high level mounting; e.g. plant rooms, atrium, warehouses etc.
- High output of 260 lumens
- 4100K 'cool' white colour temperature

Body

- Recessed and surface mounted options
- For mounting up to 10m high
- Cast aluminium body with integral heat sink
- Finished in white or silver
- Supplied complete with driver
- Input voltage 24V DC via Pathfinder system
- 5W total power including driver
- Current consumption: 0.2A
- Recessed IP20
- Surface IP40



Surface mounted, silver

Order Codes

LED Head and Driver

Recessed, 5W, white
Surface, 5W, white


PFDHRDLW
PFDHSDLW

Options


Silver Replace W with S i.e. PFDHSDL S

Dimensions

Surface



Recessed



Version	Ø	CAØ	H	KG
Surface	85	-	41	0.26
Recessed	85	68	30	0.20

Performance Guide Spacing Table

0.5 Lux minimum

Mounting height	Distance from wall	Distance between heads
3m	5.3	12.9
5m	6.3	15.9
7m	6.7	17.7
10m	6.2	19.1



To Specify

Central battery, central test LED emergency lighting system. Fully addressable LED emergency lighting points. Control unit with programmable interface – as Whitecroft Lighting PATHFINDER