

Optics

- 4 x 1W LED
- 22m viewing distance
- LEFT, RIGHT, UP and DOWN printed acrylic legend panel to be ordered separately

Body

- Brushed stainless steel body housing LEDs and electronics
- Three mounting options:
 - Ceiling
 - Wall
 - Suspended (Supplied with 1m wire suspension kit)
- Input voltage 24V DC
- Supplied complete with driver
- Current consumption: 0.2A

Note: LED architectural exit sign can only be used as part of a Pathfinder system



Order Codes

Architectural Exit Sign


4 x 1W LED	Ceiling Mounted	PFDCEILING/ARCH
4 x 1W LED	Wall Mounted	PFDWALL/ARCH
4 x 1W LED	Suspended	PFDSUSPENDED/ARCH

Legends

DOWN LEGEND	SINGLE SIDED	PFDARCHSSD
UP LEGEND	SINGLE SIDED	PFDARCHSSU
LEFT LEGEND	SINGLE SIDED	PFDARCHSSL
RIGHT LEGEND	SINGLE SIDED	PFDARCHSSR
DOWN LEGEND	DOUBLE SIDED	PFDARCHDSD
UP LEGEND	DOUBLE SIDED	PFDARCHDSU
TO SIDE LEGEND	DOUBLE SIDED	PFDARCHDST

Note: Legends to be ordered separately

Dimensions



L	W	H	KG
286	55	231	1.95

Legends



Up



Down



Left



Right

To Specify

Central battery, central test LED emergency lighting system. Fully addressable LED emergency lighting points. Control unit with programmable interface – as Whitecroft Lighting PATHFINDER