

Optics

- 22m viewing distance
 - 6 x 0.5W LEDs
- LEFT, RIGHT, UP and DOWN printed acrylic legend panel to be ordered separately

Body

- Extruded aluminium body housing electronics and LEDs
- Three mounting options:
 - Ceiling
 - Wall
 - Suspended (Supplied with 1m wire suspension kit)
- Input voltage 24V DC
- Supplied complete with driver
- Current consumption:
 - 22m: 0.125A

Note: LED exit sign can only be used as part of a Pathfinder system



Wall Mount



Ceiling Mount

Order Codes

LED Exit Sign 16m


4 x 0.5W LED	Ceiling Mounted	PFDCEILING/22M
4 x 0.5W LED	Wall Mounted	PFDWALL/22M
4 x 0.5W LED	Suspended	PFDSUSPENDED/22M

Legends

DOWN LEGEND	SINGLE SIDED	PFDLPSSD/22M
UP LEGEND	SINGLE SIDED	PFDLPSSU/22M
LEFT LEGEND	SINGLE SIDED	PFDLPSSL/22M
RIGHT LEGEND	SINGLE SIDED	PFDLPSSR/22M
DOWN LEGEND	DOUBLE SIDED	PFDLPDSD/22M
UP LEGEND	DOUBLE SIDED	PFDLPDSU/22M
TO SIDE LEGEND	DOUBLE SIDED	PFDLPDST/22M

Note: Legends to be ordered separately

Dimensions



Version	L	W	H	KG
16m	176	28	134	0.6
22m	256	28	180	0.9

Legends



Up



Down



Left



Right

To Specify

Central battery, central test LED emergency lighting system. Fully addressable LED emergency lighting points. Control unit with programmable interface – as Whitecroft Lighting PATHFINDER